
HONOR S N WHITE OPTIC LED

180 variants



Dimensions



Available colours

White | Black | Grey | Chrome | Nickel

HONOR S N WHITE OPTIC LED is a recessed ceiling luminaire with an aluminium body and 172 mm diameter. It suits homes, offices, hotels and commercial spaces where the ceiling needs to remain clean and the lighting should integrate quietly into the architecture. As the smaller version of the series, it suits areas that need a lighter visual presence without changing the design approach. It is available in white, black, grey, nickel and chrome finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. The recessed installation keeps the ceiling clean and allows the luminaire to work without drawing excessive attention.

LUMINAIRE POWER

12.9 - 31.1 W

LUMINAIRE LUMINOUS FLUX

1,187 - 2,633 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of HONOR S N WHITE OPTIC LED.

Mounting position	**Ceiling Recessed**
Housing	**Aluminium**
Optic	**Prismatic glass**
Light source	**COB LED**
Body dimensions	**Ø 172 × 110 mm**
Control Gear	**Remote Electronic Driver**
Colour uniformity	**3 SDCM**
Ripple	**3**
Operating voltage	**34.6 V**

Power factor	**0.96**
Protection rating	**IP40 / IK04**
Insulation class	**Class III**
Lifetime	**>60.000h L80B10@35°C**
Operating temperature	**-10…+45°C**
Operating humidity	**5…95%**
Lighting direction	**Downwards**
Accessories	**CONVERSIONKIT & BATTERY, CEILING SUSPENSION, CLIPS, LED PANEL BOX**

Markings and catalogue references	**CE • LM80 • LM79 • TM21 • REACH • ENEC • CB**

Options per version

Beams 60° (XW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 80.6 - 96.7 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	60°	12.9 - 31.1	**1,187 - 2,505**
935	3500 K	60°	12.9 - 31.1	**1,217 - 2,569**
940	4000 K	60°	12.9 - 31.1	**1,247 - 2,633**

Luminous flux range per version

Minimum 1,187 lm / 12.9 W / 930 / DL5225CL001ON

Maximum 2,633 lm / 31.1 W / 940 / DL5232CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >