BENE 2F L

162 variants



Dimensions



Available colours

White **Black** **Grey**

BENE 2F L is a ceiling luminaire with an aluminium body and 36 mm width, 130 mm height. It can be used in projects that require a clean appearance, reliable operation and adaptation to the needs of the space. Its medium scale offers more light quantity and a larger body than the simpler versions, while keeping a related appearance within the series. As a larger version of the series, it provides more presence and light quantity for larger spaces or more demanding areas. The deep anti-glare optical system reduces the visibility of the light source and helps keep the light comfortable in everyday use. Low glare combined with CRI90 makes it suitable for projects with high visual-comfort requirements, including offices, hospitality spaces and WELL or LEED-oriented applications. It is available in white, black and grey finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects.

LUMINAIRE POWER

2.2 - 3.2 W

LUMINAIRE LUMINOUS FLUX

194 - 306 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of BENE 2F L.

Mounting position	**Ceiling**	Operating voltage	**230 V**
Housing	**Aluminium**	Power factor	**0.96**
Optic	**PMMA**	Protection rating	**IP20 / IK04**
Light source	**Linear LED**	Insulation class	**Class I**
Body dimensions	**36 × 66 × 130 mm**	Lifetime	**>60.000h L80B10@35°C**
Control Gear	**Remote Electronic Driver**	Operating temperature	**-10…+45°C**
Colour uniformity	**3 SDCM**	Operating humidity	**5…95%**
Ripple	**3**	Lighting direction	**Downwards**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 15° (N), 30° (M), 45° (W) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 84.1 - 100.5 lm/W | UGR longwise / parallel 7 - 15 / 5 - 13

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	15°, 30°, 45°	2.2 - 3.2	**194 - 269**
930	3000 K	15°, 30°, 45°	2.2 - 3.2	**209 - 290**
940	4000 K	15°, 30°, 45°	2.2 - 3.2	**221 - 306**

Luminous flux range per version

Minimum 194 lm / 2.2 W / 927 / CM0019CL001ON

Maximum 306 lm / 3.2 W / 940 / CM0032CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >