BENE 5F L ASYMMETRIC

108 variants



Dimensions



Available colours

White **Black** **Grey**

BENE 5F L ASYMMETRIC is a surface-mounted ceiling LED luminaire with an aluminium body. Its asymmetric optic directs light to one side for lighting walls and vertical surfaces. Dimensions, power and control options are listed in the technical data for each variant. Body dimensions: 138×36×130 mm. The corresponding dimensions are listed for each variant.

LUMINAIRE POWER

5.5 - 8 W

LUMINAIRE LUMINOUS FLUX

280 - 444 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of BENE 5F L ASYMMETRIC.

Mounting position	**Ceiling**	Ripple	**3**
Housing	**Aluminium**	Power factor	**0.96**
Optic	**PMMA**	Protection rating	**IP20 / IK04**
Light source	**Linear LED**	Lifetime	**>60.000h L80B10@35°C**
Body dimensions	**36 × 138 × 130 mm**	Operating temperature	**-10…+45°C**
Control Gear	**Built-in ECG**	Operating humidity	**5…95%**
Colour uniformity	**3 SDCM**	Lighting direction	**Downwards**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams - (ASY), 81° (ASY) | Control On-Off, DALI2, DALI2 + Casambi | Operating voltage 15 V, 230 V | Insulation class Class III, Class I

Luminous efficacy 48.5 - 58.4 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	-, 81°	5.5 - 8	**280 - 388**
930	3000 K	-, 81°	5.5 - 8	**307 - 425**
940	4000 K	-, 81°	5.5 - 8	**321 - 444**

Luminous flux range per version

Minimum 280 lm / 5.5 W / 927 / DL0091CL001ON

Maximum 444 lm / 8 W / 940 / DL0096CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >