
BENE 5F S ASYMMETRIC

81 variants



Dimensions



Available colours

White **Black** **Grey**

BENE 5F S ASYMMETRIC is a ceiling luminaire with an aluminium body and 36 mm width, 70 mm height. It can be used in projects that require a clean appearance, reliable operation and adaptation to the needs of the space. As a larger version of the series, it provides increased light quantity and a stronger presence, while remaining easy to combine with smaller versions of the same family in one project. As the smaller version of the series, it suits areas that need a lighter visual presence without changing the design approach. The asymmetric distribution directs light to one side, helping with walls, circulation areas, shelving or layouts where the light needs to work off-axis. It is available in white, black and grey finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects.

LUMINAIRE POWER

5.5 - 11.6 W

LUMINAIRE LUMINOUS FLUX

280 - 593 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of BENE 5F S ASYMMETRIC.

Mounting position	**Ceiling**	Operating voltage	**230 V**
Housing	**Aluminium**	Power factor	**0.96**
Optic	**PMMA**	Protection rating	**IP20 / IK04**
Light source	**Linear LED**	Insulation class	**Class I**
Body dimensions	**36 × 138 × 70 mm**	Lifetime	**>60.000h L80B10@35°C**
Control Gear	**Remote Electronic Driver**	Operating temperature	**-10…+45°C**
Colour uniformity	**3 SDCM**	Operating humidity	**5…95%**
Ripple	**3**	Lighting direction	**Downwards**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 81° (ASY) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 44.7 - 58.4 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	81°	5.5 - 11.6	**280 - 519**
930	3000 K	81°	5.5 - 11.6	**307 - 569**
940	4000 K	81°	5.5 - 11.6	**321 - 593**

Luminous flux range per version

Minimum 280 lm / 5.5 W / 927 / CM0142CL001ON

Maximum 593 lm / 11.6 W / 940 / CM0150CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >