VIGOR M OUT

6 variants



Dimensions



Available colours

White

VIGOR M OUT is a ceiling luminaire with an integrated LED source, with an aluminium body and 170 mm diameter. It can be used in projects that require a clean appearance, reliable operation and adaptation to the needs of the space. As the medium version of the series, it offers more presence than the smaller versions without becoming visually heavy. The integrated LED source with CRI90 supports good colour rendering, in 3000K and 4000K colour temperatures. Special RAL colours can be requested for projects with a specific colour scheme. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects.

LUMINAIRE POWER

22 W

LUMINAIRE LUMINOUS FLUX

1,940 - 2,068 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of VIGOR M OUT.

Mounting position	**Ceiling**	Operating voltage	**230 V**
Housing	**Aluminium**	Power factor	**0.96**
Optic	**PMMA**	Protection rating	**IP54 / IK05**
Light source	**SMD LED**	Insulation class	**Class II**
Body dimensions	**Ø 170 × 40 mm**	Lifetime	**>50.000h L80B10@35°C**
Control Gear	**Built-in ECG**	Operating temperature	**-10…+45°C**
Colour uniformity	**3 SDCM**	Operating humidity	**5…95%**
Ripple	**3**	Lighting direction	**Downwards**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 115° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 88.2 - 94 lm/W | UGR longwise / parallel 29 / 29

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	115°	22	**1,940**
940	4000 K	115°	22	**2,068**

Luminous flux range per version

Minimum 1,940 lm / 22 W / 930 / CM0221CL001ON

Maximum 2,068 lm / 22 W / 940 / CM0224CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >