FIRMUS B 30

72 variants



Dimensions



Available colours

White **Black** **Grey** **Brown**

FIRMUS B 30 is a ceiling luminaire with a metal body and 345 mm diameter. It can be used in projects that require a clean appearance, reliable operation and adaptation to the needs of the space. Its anti-glare approach helps create a more comfortable lighting environment, especially in spaces where people spend longer periods of time. It is available in white, black, grey and brown finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects.

LUMINAIRE POWER

14.4 - 22.5 W

LUMINAIRE LUMINOUS FLUX

1,584 - 2,588 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of FIRMUS B 30.

Mounting position	**Ceiling**	Operating voltage	**230 V**
Housing	**Metal**	Power factor	**0.96**
Optic	**Opal Polycarbonate**	Protection rating	**IP20 / IK03**
Light source	**COB LED**	Insulation class	**Class I**
Body dimensions	**Ø 345 × 80 mm**	Lifetime	**>80.000h L80B10@35°C**
Control Gear	**Built-in ECG**	Operating temperature	**-10…+45°C**
Colour uniformity	**3 SDCM**	Operating humidity	**5…95%**
Ripple	**3**	Lighting direction	**Downwards**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 115° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 110 - 115 lm/W | UGR longwise / parallel 21 - 23 / 21 - 23

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	115°	14.4 - 22.5	**1,584 - 2,475**
940	4000 K	115°	14.4 - 22.5	**1,656 - 2,588**

Luminous flux range per version

Minimum 1,584 lm / 14.4 W / 930 / CM0244CL001ON

Maximum 2,588 lm / 22.5 W / 940 / CM0249CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >