
FIGO DZ UP DOWN

24 variants



Dimensions



Available colours

White **Black**

FIGO DZ UP DOWN is a ceiling luminaire with an aluminium body and 400–600 mm diameter. It can be used in projects that require a clean appearance, reliable operation and adaptation to the needs of the space. Its anti-glare approach helps create a more comfortable lighting environment, especially in spaces where people spend longer periods of time. It is available in black and white finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects.

LUMINAIRE POWER

40 - 60 W

LUMINAIRE LUMINOUS FLUX

2,960 - 5,040 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of FIGO DZ UP DOWN.

Mounting position	**Ceiling**	Ripple	**3**
Housing	**Aluminium**	Power factor	**0.96**
Optic	**Microprismatic**	Protection rating	**IP40**
Light source	**Linear LED**	Operating temperature	**-10…+45°C**
Control Gear	**Built-in ECG**	Operating humidity	**5…95%**
Colour uniformity	**3 SDCM**	Lighting direction	**Upwards & downwards**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 93° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 74 - 84 lm/W | UGR longwise / parallel 19 - 20 / 19 - 20 | Height 50 mm | Diameter 400 - 600 mm

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	93°	40 - 60	**2,960 - 4,800**
940	4000 K	93°	40 - 60	**3,136 - 5,040**

Luminous flux range per version

Minimum 2,960 lm / 40 W / 930 / CM0423CL002ON

Maximum 5,040 lm / 60 W / 940 / CM0426CL002ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >