
NOVITAS 3

720 variants



Dimensions



Available colours

White **Black** **Grey** **Copper**

It is suitable for offices, retail spaces, hospitality, homes and architectural compositions where the light line becomes part of the spatial layout. In suspended versions, suspension and feed points can be planned according to the project supply position, helping the linear run sit correctly in the space. It is available in white, black, copper and grey finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. The suspended installation makes it useful when the luminaire needs to define a zone, such as a table, worktop or central area of the space. Lengths vary by version. The profile cross-section is 84 mm wide and 74 mm high.

LUMINAIRE POWER

11.3 - 135.1 W

LUMINAIRE LUMINOUS FLUX

1,120 - 14,221 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of NOVITAS 3.

Mounting position	**Pendant**
Housing	**Aluminium**
Optic	**PMMA**
Light source	**Linear LED**
Control Gear	**Built-in ECG**
Colour uniformity	**3 SDCM**
Ripple	**3**
Operating voltage	**230 V**

Power factor	**0.96**
Protection rating	**IP40 / IK04**
Insulation class	**Class I**
Lifetime	**>80.000h L80B10@35°C**
Operating temperature	**-10…+45°C**
Operating humidity	**5…95%**
Lighting direction	**Downwards**
Accessories	**AUTO WIRE SUPPORT BLOCK, TUBOCOVER**

Markings and catalogue references	**CE • LM80 • LM79 • TM21 • REACH • ENEC**

Options per version

Beams 115° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 97.9 - 105.4 lm/W | UGR longwise / parallel 24 - 25 / 24 - 26 | Length 580 - 4,500 mm | Width 84 mm | Height 74 mm

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	115°	11.3 - 135.1	**1,120 - 13,437**
940	4000 K	115°	11.3 - 135.1	**1,190 - 14,221**

Luminous flux range per version

Minimum 1,120 lm / 11.3 W / 930 / PRS0009CL001ON

Maximum 14,221 lm / 135.1 W / 940 / PRS0068CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >