FUGA 2 CURVE SP

12 variants



Dimensions



Available colours

White **Black**

Layouts can be configured using 135°, 120°, 60°, 45° and 30° connectors. Profiles are available with a height of 100 or 140 mm; this technical reference uses the 100 mm version. Available in 3000K and 4000K, white or black, with On-Off, DALI2 or DALI2 with Casambi.

LUMINAIRE POWER

18.8 W

LUMINAIRE LUMINOUS FLUX

1,507 - 1,695 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of FUGA 2 CURVE SP.

Mounting position	**Pendant**
Housing	**Aluminium**
Optic	**PMMA**
Light source	**Linear LED**
Body dimensions	**100 × 1000 × 100 mm**
Control Gear	**Built-in ECG**
Operating voltage	**230 V**
Power factor	**0.96**

Protection rating	**IP40 / IK04**
Insulation class	**Class I**
Lifetime	**>80.000h L80B10@35°C**
Operating temperature	**-10…+45°C**
Operating humidity	**5…95%**
Lighting direction	**Downwards**
Accessories	**AUTO WIRE SUPPORT BLOCK, CONVERSIONKIT+BATTERY**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 80 - 90 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K		18.8	**1,507**
940	4000 K		18.8	**1,695**

Luminous flux range per version

Minimum 1,507 lm / 18.8 W / 930 / PRS0069CL001ON

Maximum 1,695 lm / 18.8 W / 940 / PRS2019CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >