FUGA 2 RING SP

288 variants



Dimensions



Available colours

White **Black** **Grey**

FUGA 2 RING SP is a suspended linear luminaire with an aluminium body and 100 mm height. It is suitable for offices, retail spaces, hospitality, homes and architectural compositions where the light line becomes part of the spatial layout. In suspended versions, suspension and feed points can be planned according to the project supply position, helping the linear run sit correctly in the space. Low glare combined with CRI90 makes it suitable for projects with high visual-comfort requirements, including offices, hospitality spaces and WELL or LEED-oriented applications. It is available in white, black and grey finishes, with special RAL colours available on request for project-specific schemes. On-Off, DALI2 and Casambi options allow the luminaire to support anything from simple operation to more advanced lighting control in professional projects. The suspended installation makes it useful when the luminaire needs to define a zone, such as a table, worktop or central area of the space.

LUMINAIRE POWER

35.5 - 186.6 W

LUMINAIRE LUMINOUS FLUX

2,840 - 17,914 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of FUGA 2 RING SP.

Mounting position	**Pendant**
Housing	**Aluminium**
Optic	**PMMA**
Light source	**Linear LED**
Control Gear	**Built-in ECG**
Colour uniformity	**3 SDCM**
Ripple	**3**
Operating voltage	**230 V**

Power factor	**0.96**
Protection rating	**IP40 / IK04**
Insulation class	**Class I**
Lifetime	**>80.000h L80B10@35°C**
Operating temperature	**-10…+45°C**
Operating humidity	**5…95%**
Lighting direction	**Downwards**
Accessories	**AUTO WIRE SUPPORT BLOCK, CONVERSIONKIT+BATTERY**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 110° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 80 - 96 lm/W | UGR longwise / parallel 17 - 22 / 17 - 22 | Height 100 mm | Diameter 600 - 2,000 mm

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	110°	35.5 - 186.6	**2,840 - 16,048**
940	4000 K	110°	35.5 - 186.6	**3,195 - 17,914**

Luminous flux range per version

Minimum 2,840 lm / 35.5 W / 930 / PRS0086CL001ON

Maximum 17,914 lm / 186.6 W / 940 / PRS0117CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >