NOVUS OUT OPAL TAPE LED

144 variants



Dimensions



Available colours

White **Black** **Grey** **Anodized aluminium**

The NOVUS OUT OPAL TAPE LED mounts directly to the ceiling or wall, depending on the bracket. It has an aluminium body, an opal PMMA diffuser and a linear LED source. With the ceiling bracket, the installed width and height are 29.5 × 53 mm. Catalogue variants measure 100, 500 or 1,000 mm and offer 3000 or 4000 K light with CRI90. The profile is available in lengths up to 4.5 m. Available in white, black and grey, as well as anodized aluminium. Control options are listed by product code. Compatible accessories are SKB 12, SKB 21 and SKB 50. Protection rating IP68.

LUMINAIRE POWER

1 - 15 W

LUMINAIRE LUMINOUS FLUX

55 - 1,050 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of NOVUS OUT OPAL TAPE LED.

Mounting position	**Ceiling**	Power factor	**0.96**
Housing	**Aluminium**	Protection rating	**IP68 / IK10**
Optic	**PMMA**	Insulation class	**Class III**
Light source	**Linear LED**	Lifetime	**>50.000h L70B10@35°C**
Control Gear	**Remote Electronic Driver**	Operating temperature	**-10…+45°C**
Colour uniformity	**3 SDCM**	Operating humidity	**5…95%**
Ripple	**3**	Lighting direction	**Downwards**
Operating voltage	**24 V**	Accessories	**SKB 12, SKB 21, SKB 50**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 119° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 55 - 70.7 lm/W | UGR longwise / parallel 26 - 28 / 27 - 29 | Length 100 - 1,000 mm | Width 29.5 mm | Height 53 mm

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	119°	1 - 15	**55 - 825**
940	4000 K	119°	1 - 15	**70 - 1,050**

Luminous flux range per version

Minimum 55 lm / 1 W / 930 / PRC1749CL001ON

Maximum 1,050 lm / 15 W / 940 / PRC1760CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >