NOTUS 25 OUT

540 variants



Dimensions



Available colours

White **Black** **Grey**

NOTUS 25 OUT is a surface-mounted linear luminaire for ceilings or walls, with an aluminium body and a PMMA diffuser. It delivers continuous light along the profile. A range of lengths and finishes is available, with On-Off, DALI2 and Casambi options depending on the product code.

LUMINAIRE POWER

11.3 - 135.1 W

LUMINAIRE LUMINOUS FLUX

857 - 10,853 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of NOTUS 25 OUT.

Mounting position	**Ceiling, Wall Mounted**	Power factor	**0.96**
Housing	**Aluminium**	Protection rating	**IP54 / IK04**
Optic	**PMMA**	Insulation class	**Class I**
Light source	**Linear LED**	Lifetime	**>80.000h L80B10@35°C**
Control Gear	**Built-in ECG**	Operating temperature	**-10…+45°C**
Colour uniformity	**3 SDCM**	Operating humidity	**5…95%**
Ripple	**3**	Lighting direction	**Sideways**
Operating voltage	**230 V**	Accessories	**CONVERSION KIT + BATTERY**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 105° (VW) | Control On-Off, DALI2, DALI2 + Casambi

Luminous efficacy 75.5 - 80.4 lm/W | UGR longwise / parallel 24 - 26 / 24 - 26 | Length 585 - 4,536 mm | Width 46 mm | Height 71 mm

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K	105°	11.3 - 135.1	**857 - 10,282**
940	4000 K	105°	11.3 - 135.1	**908 - 10,853**

Luminous flux range per version

Minimum 857 lm / 11.3 W / 930 / PRC1689CL001ON

Maximum 10,853 lm / 135.1 W / 940 / PRC1748CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >