
NOTUS 11 ASYMMETRIC

540 variants



Dimensions



Available colours

White **Black** **Grey**

NOTUS 11 ASYMMETRIC is a surface-mounted linear ceiling luminaire with an aluminium body and a wedge-shaped cross-section, 55 mm wide and 76 mm high. It is available in 15 reference lengths from 600 to 4555 mm, with two power levels per length. The asymmetric ASY distribution directs light towards one side for vertical surfaces and linear areas, according to the lighting design. The 3000 and 4000 K options with CRI90 are available with textured white, black or grey finishes. Control is available through On-Off, DALI2 or DALI2 with Casambi. The luminaire is intended for indoor use, with an IP30 rating and IK06 impact protection.

LUMINAIRE POWER

12.6 - 137.7 W

LUMINAIRE LUMINOUS FLUX

1,449 - 17,497 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of NOTUS 11 ASYMMETRIC.

Mounting position	**Ceiling**
Housing	**Aluminium**
Light source	**Linear LED**
Control Gear	**Built-in ECG**
Colour uniformity	**3 SDCM**
Ripple	**3**
Operating voltage	**230 V**
Power factor	**0.96**

Protection rating	**IP30 / IK06**
Insulation class	**Class I**
Lifetime	**>80.000h L80B10@35°C**
Operating temperature	**-10…+45°C**
Operating humidity	**5…95%**
Lighting direction	**Downwards**
Accessories	**AUTO WIRE SUPPORT BLOCK, CONVERSIONKIT+BATTERY**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams (ASY) | Control DALI2, DALI2 + Casambi, On-Off

Luminous efficacy 115 - 127.2 lm/W | Length 600 - 4,555 mm | Width 55 mm | Height 76 mm

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
930	3000 K		12.6 - 137.7	**1,449 - 16,641**
940	4000 K		12.6 - 137.7	**1,523 - 17,497**

Luminous flux range per version

Minimum 1,449 lm / 12.6 W / 930 / PRC1777CL001DA

Maximum 17,497 lm / 137.7 W / 940 / PRC1836CL001DA

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >