TERES 1 CEILING BRASS LED

72 variants



Dimensions



Available colours

White Black Grey Anthracite

TERES 1 CEILING BRASS LED is surface mounted on the ceiling and directs light downwards. Its brass housing is 60 mm in diameter and 100 mm high, with clear safety glass. Available in white, black, grey and anthracite, with 3.36 or 4.86 W power, CRI90 and a choice of 2700, 3000 or 4000 K. Beam options are 8°, 25° or 45°, with On-Off control. Protection rating IP67 and impact resistance IK07.

LUMINAIRE POWER

3.4 - 4.9 W

LUMINAIRE LUMINOUS FLUX

338 - 528 lm

The power and luminous flux ranges are calculated separately from the listed variants. For an exact combination, see the code details on the site.

See all variants on bright.gr >

Technical characteristics

Common data

Characteristics that apply to all versions of TERES 1 CEILING BRASS LED.

Mounting position	**Ceiling**	Body dimensions	**Ø 60 × 100 mm**
Housing	**Brass**	Protection rating	**IP67 / IK07**
Optic	**Safety Glass Clear**	Lighting direction	**Downwards**
Light source	**H.P. LED**	Accessories	**MOUNTING SET**

Markings and catalogue references **CE • LM80 • LM79 • TM21 • REACH**

Options per version

Beams 8° (UN), 25° (NM), 45° (W) | Control On-Off

Luminous efficacy 96.3 - 116.4 lm/W

CRI/CCT	Colour temperature	Beams	Power (W)	Luminous flux (lm)
927	2700 K	8°, 25°, 45°	3.4 - 4.9	**338 - 468**
930	3000 K	8°, 25°, 45°	3.4 - 4.9	**355 - 492**
940	4000 K	8°, 25°, 45°	3.4 - 4.9	**391 - 528**

Luminous flux range per version

Minimum 338 lm / 3.4 W / 927 / CM0891CL001ON

Maximum 528 lm / 4.9 W / 940 / CM0906CL001ON

The ranges per CCT summarise the values of the available codes. To choose a specific code, open the full table of variants.

See all variants on bright.gr >