
HEADOFFICE: Showroom 13 Sofokli Venizelou Ave., Likovrisi, P.O. Box 14123, Athens, Greece Tel: (+30) 210 2851 304 I www.bright.gr I info@bright.gr

NOTUS 5 SQUARE SP



Technical drawings



L: 640x640mm - 25.19''x25.19''
925x925mm - 36.41''x36.41''
1205x1205mm - 47.44''x47.44''
1490x1490mm - 58.66''x58.66''

Product Details

CE LM80 LM79 TM21 REACH Source Type Linear LED

General Information

Housing	Aluminium
Product code	PRS1167CL001ON
Product family	NOTUS
Diffuser	PMMA
Control Gear	Built-in ECG
Width	3990 mm
Length	3990 mm
Height	87 mm


Electrical data

Consumption	472,8 W
Performance	90.07 lm/W
Ripple	3
Power Factor	0.96
Nominal Voltage	230 V

Luminaire Output

Beam Type	VW
Beam	104º
Luminous Flux	42552 lm
CRI CCT	930

Light distribution



Safety characteristics

IK	04
IP	40
Protection Class	Class I

Temperature Operating Conditions

Lifetime	>80.000h L80B10@35°C
Operating Ambient Temperature	-10...+45°C
Operating Humidity Level	5...95%