
# COMIS 5 II SP






CE LM80 LM79 TM21 REACH CE LM8

TM21 REACH Source Type Linear LED

## Product Details

### General Information

| | |
|---|---|
| Housing | Aluminium |
| Product code | PRS1917CL003DA |
| Product family | COMIS |
| Diffuser | |
| Control Gear | Built-in ECG |
| Width | 113 |
| Length | 1000 |
| Height | 79 |


### Electrical data

| | |
|---|---|
| Consumption | 19,2 |
| Performance | 55 |
| Ripple | 3 |
| Power Factor | 0.96 |
| Nominal Voltage | 230 |

### Luminaire Output

| | |
|---|---|
| Beam Type | VW |
| Beam | 360º |
| Luminous Flux | 1056 |
| CRI CCT | 930 |
| Glare Indicator Ugr Longwise Optics | 12 |
| Glare Indicator Ugr Parallel Optics | 13 |

### Light distribution




### Safety characteristics

| | |
|---|---|
| IK | 05 |
| IP | 40 |
| Protection Class | Class I |

### Temperature Operating Conditions

| | |
|---|---|
| Lifetime | >50.000h L70B10@35°C |
| Operating Ambient Temperature | -10...+45°C |
| Operating Humidity Level | 5...95% |