
# FUGA 2 SQUARE






## Product Details

CE LM80 LM79 TM21 REACH

Source Type Linear LED

### General Information

| | |
|---|---|
| Housing | Aluminium |
| Product code | PRC0082CL002DA |
| Product family | FUGA |
| Diffuser | PMMA |
| Control Gear | Built-in ECG |
| Width | 650 |
| Length | 650 |
| Height | 140 |


### Electrical data

| | |
|---|---|
| Consumption | 51,2 |
| Performance | 85.37 |
| Ripple | 3 |
| Power Factor | 0.96 |
| Nominal Voltage | 230 |

### Luminaire Output

| | |
|---|---|
| Beam Type | VW |
| Beam | 110º |
| Luminous Flux | 4354 |
| CRI CCT | 940 |
| Glare Indicator Ugr Longwise Optics | 21 |
| Glare Indicator Ugr Parallel Optics | 20 |

### Light distribution




### Safety characteristics

| | |
|---|---|
| IK | 04 |
| IP | 40 |
| Protection Class | Class I |

### Temperature Operating Conditions

| | |
|---|---|
| Lifetime | >50.000h L70B10@35°C |
| Operating Ambient Temperature | -10...+45°C |
| Operating Humidity Level | 5...95% |