
# COMIS IN OPAL






## Product Details

CE LM80 LM79 TM21 REACH

Source Type COB LED

### General Information

| | |
|---|---|
| Housing | Aluminium |
| Product code | PRR0546CL001DA |
| Product family | COMIS |
| Diffuser | PMMA |
| Control Gear | Remote Electronic Driver |
| Width | 22.68 |
| Length | 500 |
| Height | 12.85 |


### Electrical data

| | |
|---|---|
| Consumption | 7,5 |
| Performance | 55 |
| Ripple | 3 |
| Power Factor | 0.96 |
| Nominal Voltage | 24 |

### Luminaire Output

| | |
|---|---|
| Beam Type | VW |
| Beam | 119º |
| Luminous Flux | 412.5 |
| CRI CCT | 930 |
| Glare Indicator Ugr Longwise Optics | 27 |
| Glare Indicator Ugr Parallel Optics | 28 |

### Light distribution




### Safety characteristics

| | |
|---|---|
| IK | 05 |
| IP | 40 |
| Protection Class | Class III |

### Temperature Operating Conditions

| | |
|---|---|
| Lifetime | >50.000h L70B10@35°C |
| Operating Ambient Temperature | -10...+45°C |
| Operating Humidity Level | 5...95% |