

HEADOFFICE: Showroom 13 Sofokli Venizelou Ave., Likovrisi, P.O. Box 14123, Athens, Greece Tel: (+30) 210 2851 304 I www.bright.gr I info@bright.gr

# NOTUS 25 TRIMLESS A






## Product Details

CE LM80 LM79 TM21 REACH

Source Type Linear LED

### General Information

| | |
|---|---|
| Housing | Aluminium |
| Product code | PRT0052CL002DAC |
| Product family | NOTUS |
| Diffuser | Anti-Glare PC Shade |
| Control Gear | Built-in ECG |
| Width | 49 |
| Length | 1996 |
| Height | 72 |


### Electrical data


| | |
|---|---|
| Consumption | 59,1 |
| Performance | 76.11 |
| Ripple | 3 |
| Power Factor | 0.96 |
| Nominal Voltage | 230 |


### Luminaire Output

| | |
|---|---|
| Beam Type | VW |
| Beam | 104º |
| Luminous Flux | 4498 |
| CRI CCT | 930 |
| Glare Indicator Ugr Longwise Optics | 25 |
| Glare Indicator Ugr Parallel Optics | 25 |

### Light distribution





### Safety characteristics

| | |
|---|---|
| IK | 04 |
| IP | 54 |
| Protection Class | Class I |

### Temperature Operating Conditions

| | |
|---|---|
| Lifetime | >80.000h L80B10@35°C |
| Operating Ambient Temperature | -10...+45°C |
| Operating Humidity Level | 5...95% |