
HEADOFFICE: Showroom 13 Sofokli Venizelou Ave., Likovrisi, P.O. Box 14123, Athens, Greece Tel: (+30) 210 2851 304 I www.bright.gr I info@bright.gr

# GIGA 2 LED






## Product Details

CE LM80 LM79 TM21 REACH

Source Type H.P. LED

### General Information

| | |
|---|---|
| Housing | Aluminium |
| Product code | HB0044CL003DA |
| Product family | GIGA |
| Diffuser | |
| Control Gear | |
| Height | 520 |


### Electrical data

| | |
|---|---|
| Consumption | 80 |
| Performance | 131.88 |
| Ripple | 3 |
| Power Factor | 0.96 |
| Nominal Voltage | 230 |

### Luminaire Output

| | |
|---|---|
| Beam Type | W |
| Beam | 41º |
| Luminous Flux | 10550 |
| CRI CCT | 957 |
| Glare Indicator Ugr Longwise Optics | 14 |
| Glare Indicator Ugr Parallel Optics | 22 |

### Light distribution




### Safety characteristics

| | |
|---|---|
| IK | 04 |
| IP | 54 |
| Protection Class | Class I |

### Temperature Operating Conditions

| | |
|---|---|
| Lifetime | >60.000h L80B10@35°C |
| Operating Ambient Temperature | -10...+45°C |
| Operating Humidity Level | 5...95% |