
# COMIS 4



## Technical drawings




## Product Details

CE LM80 LM79 TM21 REACH Source Type LED Strip

### General Information

| | |
|---|---|
| Housing | Aluminium |
| Product code | DEW0071CL003DAC |
| Product family | COMIS |
| Diffuser | PMMA |
| Control Gear | Remote Electronic Driver |
| Options for Dimming Control | DALI2 |
| Options for Wireless Dimming | Casambi |
| Width | 70 mm |
| Length | 1000 mm |
| Height | 29 mm |


### Electrical data

| | |
|---|---|
| Consumption | 30 W |
| Performance | 70 lm/W |
| Ripple | 3 |
| Power Factor | 0.96 |
| Nominal Voltage | 230 V |

### Luminaire Output

| | |
|---|---|
| Beam Type | VW |
| Beam | 360º |
| Luminous Flux | 2100 lm |
| CRI CCT | 940 |

### Light distribution



### Safety characteristics

| | |
|---|---|
| IK | 04 |
| IP | 40 |
| Protection Class | Class I |

### Temperature Operating Conditions

| | |
|---|---|
| Lifetime | >50.000h L70B10@35°C |
| Operating Ambient Temperature | -10...+45ºC |
| Operating Humidity Level | 5...95% |