
HEADOFFICE: Showroom 13 Sofokli Venizelou Ave., Likovrisi, P.O. Box 14123, Athens, Greece Tel: (+30) 210 2851 304 I www.bright.gr I info@bright.gr

# ROTONDA C





## Product Details

CE LM80 LM79 TM21 REACH Source Type H.P. LED

### General Information

| | |
|---|---|
| Housing | Aluminium |
| Product code | AM0171CL003DA |
| Product family | ROTONDA |
| Diffuser | Lens |
| Control Gear | Built-in ECG |
| Height | 209 |
| Diameter | 480 |


### Electrical data


| | |
|---|---|
| Consumption | 56 |
| Performance | 125 |
| Ripple | 3 |
| Power Factor | 0.96 |
| Nominal Voltage | 3 |


### Luminaire Output

| | |
|---|---|
| Beam Type | III |
| Beam | 131º |
| Luminous Flux | 7000 |
| CRI CCT | 730 |

### Light distribution







### Safety characteristics

| | |
|---|---|
| IK | 08 |
| IP | 66 |
| Protection Class | Class II |

### Temperature Operating Conditions

| | |
|---|---|
| Lifetime | >100.000h L70B10@25°C |
| Operating Ambient Temperature | -30...+45°C |
| Operating Humidity Level | 5...95% |