
HEADOFFICE: Showroom 13 Sofokli Venizelou Ave., Likovrisi, P.O. Box 14123, Athens, Greece Tel: (+30) 210 2851 304 I www.bright.gr I info@bright.gr

# POTIS L



## Technical drawings




## Product Details

CE LM80 LM79 TM21 REACH ENEC

Source Type COB LED

### General Information

| | |
|---|---|
| Housing | Aluminium |
| Product code | SP0376CL003DA |
| Product family | POTIS |
| Diffuser | Reflector |
| Control Gear | Built-in ECG |
| Height | 155 mm |
| Diameter | 90 mm |


### Electrical data

| | |
|---|---|
| Consumption | 36 W |
| Performance | 97.42 lm/W |
| Ripple | 3 |
| Power Factor | 0.96 |
| Nominal Voltage | 230 V |

### Luminaire Output

| | |
|---|---|
| Beam Type | NM |
| Beam | 24º |
| Luminous Flux | 3507 lm |
| CRI CCT | 930 |
| Glare Indicator Ugr Longwise Optics | 16 |
| Glare Indicator Ugr Parallel Optics | 16 |

### Light distribution



### Safety characteristics

| | |
|---|---|
| IK | 07 |
| IP | 20 |
| Protection Class | Class II |

### Temperature Operating Conditions

| | |
|---|---|
| Lifetime | >60.000h L80B10@35°C |
| Operating Ambient Temperature | -10...+45°C |
| Operating Humidity Level | 5...95% |