
# ARCUS PENDO 3 H.P.LED



## Technical drawings




## Product Details

CE LM80 LM79 TM21 REACH Source Type H.P. LED

### General Information

| | |
|---|---|
| Housing | Aluminium |
| Product code | SP1698CL003DAC |
| Product family | ARCUS |
| Diffuser | |
| Control Gear | |
| Height | 65 mm |
| Diameter | 120 mm |


### Electrical data


| | |
|---|---|
| Consumption | 11,6 W |
| Performance | 97.36 lm/W |
| Ripple | 3 |
| Power Factor | 0.96 |
| Nominal Voltage | 230 V |

### Luminaire Output

| | |
|---|---|
| Beam Type | UN |
| Beam | 8º |
| Luminous Flux | 1071 lm |
| CRI CCT | 930 |
| Glare Indicator Ugr Longwise Optics | 9 |
| Glare Indicator Ugr Parallel Optics | 9 |

### Light distribution





### Safety characteristics

| | |
|---|---|
| IK | 02 |
| IP | 20 |
| Protection Class | Class II |

### Temperature Operating Conditions

| | |
|---|---|
| Lifetime | >60.000h L80B10@35°C |
| Operating Ambient Temperature | -10...+45°C |
| Operating Humidity Level | 5...95% |