
# LEGATUS LINEAR LED



## Technical drawings




## Product Details

CE LM80 LM79 TM21 REACH Source Type Linear LED

### General Information

| | |
|---|---|
| Housing | Aluminium |
| Product code | LV0069CL003DA |
| Product family | LEGATUS |
| Diffuser | PMMA |
| Control Gear | Built-in ECG |
| Width | 22 mm |
| Length | 850 mm |
| Height | 24 mm |


### Electrical data

| | |
|---|---|
| Consumption | 17,8 W |
| Performance | 96.35 lm/W |
| Ripple | 3 |
| Power Factor | 0.96 |
| Nominal Voltage | 48 V |

### Luminaire Output

| | |
|---|---|
| Beam Type | VW |
| Beam | 108º |
| Luminous Flux | 1638 lm |
| CRI CCT | 927 |
| Glare Indicator Ugr Longwise Optics | 28 |
| Glare Indicator Ugr Parallel Optics | 28 |

### Light distribution



### Safety characteristics

| | |
|---|---|
| IK | 05 |
| IP | 40 |
| Protection Class | Class III |

### Temperature Operating Conditions

| | |
|---|---|
| Lifetime | >60.000h L80B10@35°C |
| Operating Ambient Temperature | -10...+45°C |
| Operating Humidity Level | 5...95% |