
HEADOFFICE: Showroom 13 Sofokli Venizelou Ave., Likovrisi, P.O. Box 14123, Athens, Greece Tel: (+30) 210 2851 304 I www.bright.gr I info@bright.gr

# RITUS 50






## Product Details

CE LM80 LM79 TM21 REACH

Source Type COB LED

### General Information

| | |
|---|---|
| Housing | Aluminium |
| Product code | DL1460CL001DA |
| Product family | RITUS |
| Diffuser | |
| Control Gear | Remote Electronic Driver |
| Height | 74 |
| Diameter | 52 |


### Electrical data

| | |
|---|---|
| Consumption | 8 |
| Performance | 100.13 |
| Ripple | 3 |
| Power Factor | 0.96 |
| Nominal Voltage | 230 |

### Luminaire Output

| | |
|---|---|
| Beam Type | M |
| Beam | 30º |
| Luminous Flux | 801 |
| CRI CCT | 927 |
| Glare Indicator Ugr Longwise Optics | 16 |
| Glare Indicator Ugr Parallel Optics | 16 |

### Light distribution




### Safety characteristics

| | |
|---|---|
| IK | 04 |
| IP | 54 |
| Protection Class | Class III |

### Temperature Operating Conditions

| | |
|---|---|
| Lifetime | 20.000h |
| Operating Ambient Temperature | -10...+45°C |
| Operating Humidity Level | 5...95% |