
# MAX ARTUS H.P.LED






CE LM80 LM79 TM21 REACH CE LM8

TM21 REACH Source Type H.P. LED

## Product Details

### General Information

| | |
|---|---|
| Housing | Aluminium |
| Product code | DL1762CL001DAC |
| Product family | ARTUS |
| Diffuser | Clear Polycarbonate |
| Control Gear | Remote Electronic Driver |
| Height | 70 |
| Diameter | 160 |


### Electrical data


| | |
|---|---|
| Consumption | 11,7 |
| Performance | 104.5 |
| Ripple | 3 |
| Power Factor | 0.96 |
| Nominal Voltage | 21 |


### Luminaire Output

| | |
|---|---|
| Beam Type | NM |
| Beam | 25º |
| Luminous Flux | 1149.5 |
| CRI CCT | 940 |
| Glare Indicator Ugr Longwise Optics | 13 |
| Glare Indicator Ugr Parallel Optics | 13 |

### Light distribution





### Safety characteristics

| | |
|---|---|
| IK | 05 |
| IP | 20 |
| Protection Class | Class III |

### Temperature Operating Conditions

| | |
|---|---|
| Lifetime | >60.000h L80B10@35°C |
| Operating Ambient Temperature | -10...+45°C |
| Operating Humidity Level | 5...95% |