
HEADOFFICE: Showroom 13 Sofokli Venizelou Ave., Likovrisi, P.O. Box 14123, Athens, Greece Tel: (+30) 210 2851 304 I www.bright.gr I info@bright.gr

# SINUS 4






## Product Details

CE LM80 LM79 TM21 REACH

Source Type COB LED

### General Information

| | |
|---|---|
| Housing | Aluminium |
| Product code | DL2580CL002ON |
| Product family | SINUS |
| Diffuser | |
| Control Gear | Remote Electronic Driver |
| Height | 60 |
| Diameter | 85 |


### Electrical data

| | |
|---|---|
| Consumption | 9,2 |
| Performance | 108 |
| Ripple | 3 |
| Power Factor | 0.96 |
| Nominal Voltage | 34.6 |

### Luminaire Output

| | |
|---|---|
| Beam Type | ASY |
| Beam | - |
| Luminous Flux | 972 |
| CRI CCT | 930 |

### Light distribution




### Safety characteristics

| | |
|---|---|
| IK | 05 |
| IP | 20 |
| Protection Class | Class III |

### Temperature Operating Conditions

| | |
|---|---|
| Lifetime | >60.000h L80B10@35°C |
| Operating Ambient Temperature | -10...+45°C |
| Operating Humidity Level | 5...95% |