
# NOVITAS 2






## Product Details

CE LM80 LM79 TM21 REACH ENEC

Source Type
Linear LED

### General Information

| | |
|---|---|
| Housing | Aluminium |
| Product code | PRS0005CL001ON |
| Product family | NOVITAS |
| Diffuser | PMMA |
| Control Gear | Built-in ECG |
| Width | 45 |
| Length | 1000 |
| Height | 38 |


### Electrical data


| | |
|---|---|
| Consumption | 9,6 |
| Performance | 77.78 |
| Ripple | 3 |
| Power Factor | 0.96 |
| Nominal Voltage | 24 |


### Luminaire Output

| | |
|---|---|
| Beam Type | VW |
| Beam | 115º |
| Luminous Flux | 700 |
| CRI CCT | 930 |
| Glare Indicator Ugr Longwise Optics | 24 |
| Glare Indicator Ugr Parallel Optics | 24 |

### Light distribution





### Safety characteristics

| | |
|---|---|
| IK | 05 |
| IP | 40 |
| Protection Class | Class III |

### Temperature Operating Conditions

| | |
|---|---|
| Lifetime | >50.000h L70B10@35°C |
| Operating Ambient Temperature | -10...+45°C |
| Operating Humidity Level | 5...95% |