
HEADOFFICE: Showroom 13 Sofokli Venizelou Ave., Likovrisi, P.O. Box 14123, Athens, Greece Tel: (+30) 210 2851 304 I www.bright.gr I info@bright.gr

FUGA 2 RING SP UP DOWN



Technical drawings



Product Details

CE LM80 LM79 TM21 REACH

Source Type
Linear LED

General Information

Housing	Aluminium
Product code	PRS0150CL003DAC
Product family	FUGA
Diffuser	PMMA
Control Gear	Built-in ECG
Height	100 mm
Diameter	2000 mm


Electrical data


Consumption	385,5 W
Performance	75.1 lm/W
Ripple	3
Power Factor	0.96
Nominal Voltage	230 V

Luminaire Output

Beam Type	VW
Beam	360º
Luminous Flux	28913 lm
CRI CCT	940
Glare Indicator Ugr Longwise Optics	12
Glare Indicator Ugr Parallel Optics	13

Light distribution





Safety characteristics

IK	04
IP	40
Protection Class	Class I

Temperature Operating Conditions

Lifetime	UP: >50.000h L70B10@35°C DOWN:>80.000h L80B10@35°C
Operating Ambient Temperature	-10...+45°C
Operating Humidity Level	5...95%