
HEADOFFICE: Showroom 13 Sofokli Venizelou Ave., Likovrisi, P.O. Box 14123, Athens, Greece Tel: (+30) 210 2851 304 I www.bright.gr I info@bright.gr

# HONOR MT FLUXUS WHITE OPTIC LED



## Technical drawings




## Product Details

CE LM80 LM79 TM21 REACH ENEC

Source Type COB LED

### General Information

| | |
|---|---|
| Housing | Aluminium |
| Product code | DL6689CL002DA |
| Product family | HONOR |
| Diffuser | Prismatic glass |
| Control Gear | Built-in ECG |
| Height | 95 mm |
| Diameter | 200 mm |


### Electrical data

| | |
|---|---|
| Consumption | 22,7 W |
| Performance | 89.86 lm/W |
| Ripple | 3 |
| Power Factor | 0.96 |
| Nominal Voltage | 230 V |

### Luminaire Output

| | |
|---|---|
| Beam Type | XW |
| Beam | 86º |
| Luminous Flux | 1977 lm |
| CRI CCT | 935 |
| Glare Indicator Ugr Longwise Optics | 20 |
| Glare Indicator Ugr Parallel Optics | 20 |

### Light distribution



### Safety characteristics

| | |
|---|---|
| IK | 04 |
| IP | 20 |
| Protection Class | Class II |

### Temperature Operating Conditions

| | |
|---|---|
| Lifetime | 50.000h L70B50@25°C |
| Operating Ambient Temperature | -10…+45°C |
| Operating Humidity Level | 5…95% |