NOTUS 2 IN DOUBLE SATIN

INSTALLATION INSTRUCTIONS FOR LUMINAIRE NOTUS 2 IN DOUBLE SATIN

**1** *Installation*

110

167

Make hole pattern
Cut the hole on ceiling

2

90°

Carefully rotate the lamp to remove it from its sockets

3

Loosen the screws and remove the reflector

4

Pass the fixture through the hole and tighten the screw to secure it on ceiling

6

90°

After installing the fixture on ceiling, adjust the reflector in the fitting.
Install the lamps and then attach the double satin cover

5

the metal stripe is rotated to hold the fixture on ceiling

A

B

PUSH

~10~

A Tighten the screw until the luminaire is safely retained on ceiling.

B Make wiring connections.

USER INSTRUCTIONS

- The installation of the unit must be done by a qualified electrician.
- The unit must be earthed in case an earth connecting point exists.
- Ensure that the mains is switched off during servicing.
- Do not use bulb(s) bigger than the indicated on units name-plate or packaging.
- Ensure that after the installation, the unit is properly fixed and the cable clamps (if exist) are well tightened.
- Manufacturer will not accept liability for injury or damage resulting from incorrect use or installation
- The unit is not intended to operate in loop connection.
- Wall plugs and terminals are not included.

CE

Date Issued: *June 2014*

DQP
ISO 9001:2008 ISO 14000 Management System

CERTIFIED
IQNet
MANAGEMENT SYSTEM

DQP
Qualitätsmanagement
ISO 9001:2008

GreenLight