

PLANUS 13

installation instructions

☉ indoor / downlights



1 **Installation**
Cut false ceiling.

Depth **GU10** 113mm
S.S.LED 140mm

Ø160

2 Fit the luminaire in the ceiling.

3 Secure the fitting on ceiling with two (2) screws. Hold the fixture while using the drill.

4 After installing the fitting, fill the gaps on ceiling.

Then, paint the ceiling.

5 Make wiring connection (A), fit the lamp to the lampholder (B) and secure with the spring (C).

GU10

A INPUT ~220 - 240V

B lampholder

C spring

Make wiring connection (A), fit the lamp inside the luminaire (B) and secure with the spring (C).

S.S.LED

A INPUT ~220 - 240V

B luminaire

C spring

Adjust the metal strips (x2) on the fixture to fit to the false ceiling and tighten the screws (x4).

Tool accessories


6

USER INSTRUCTIONS

- The installation of the unit must be done by a qualified electrician.
- The unit must be earthed in case an earth connecting point exists.
- Ensure that the mains is switched off during servicing.
- Do not use bulb(s) bigger than the indicated on units name-plate or packaging.
- Ensure that after the installation, the unit is properly fixed and the cable clamps (if exist) are well tightened.
- Manufacturer will not accept liability for injury or damage resulting from incorrect use or installation
- The unit is not intended to operate in loop connection.
- Wall plugs and terminals are not included.
- LED modules are replaced only by the manufacturer.

CAUTION

Wear anti-static gloves before you touch LED systems



Factory

5 Kefalovrisou Str., Monomati, Acharnai, P.O. Box 13677, Athens, Greece
Tel: (+30) 210 6208 230 | E-mail: info@bright.gr | www.bright.gr